



Shell Rimula R5 E 10W-40 (CI-4/228.3)

Shell Rimula R5 E

Shell Rimula R5 E



ENERGISED PROTECTION
Adapting to your engine's changing needs

Shell Rimula R5 E
3, US 2002

Euro 2,

Shell Rimula R5 E

Shell Rimula R5 E



Shell Rimula R5 E

Shell Rimula R5 E

Euro 2, 3, US 2002

Shell Rimula R6 LM/LME.

- Cummins: CES 20078, 77, 76, 72, 71
- Mack: EO-M, EO-M+

- MAN: 3275
- MB Approval: 228.3
- Renault Trucks: RLD-2
- Volvo: VDS-3, VDS-2
- API: CI-4, CH-4, CG-4, CF-4, CF.
- ACEA: E7, E5, E3
- Global DHD-1

Shell Technical

Helpdesk

Properties	Method	Shell Rimula R5 E 10W-40 (CI-4/228.3)
		10W-40
@40°C	ASTM D445	90
@100°C	ASTM D445	13.4
@-25°C *	ASTM D5293	6600
	ASTM D2270	150
	KOH/ ASTM D2896	10
	% ASTM D874	1.2
@15°C /	ASTM D4052	0.882
	°C ASTM D92	220
	°C ASTM D97	-39

Shell.

Shell Rimula R5 E 10W-40 (CI-4/228.3)

<http://www.epc.shell.com/>

« ».